

AERO® brand aerosols are the finest available anywhere. A full range of solutions, from cleaning, to pest control. No other products can match our standards or our commitment to quality.



aero®

Open Gear Lube

• For Use on Open Gears, Chains, Cables and Wire Ropes

OPEN GEAR LUBE is an extremely tacky wear resistant lubricant. Resistant to water. Perfect for construction equipment, gears, sprockets, slow moving chains, and machinery. Prevents corrosion and resists oxidation by repelling moisture. It is perfect for 5th wheels due to its wear resistance and adhesion. Reduces down time and noise due to metal to metal contact. Provides a smooth and uniform coating for excellent lubricity and corrosion protection on machinery and various metal parts and equipment.

DIRECTIONS FOR USE

Shake well before using. Remove protective cap. Hold can 6 to 8 inches from surfaces to be sprayed. Apply an even coat to surface. Turn on machinery and allow lubricant to spread over all working surfaces. Apply a second thinner coating to insure adequate lubrication. Re-apply as needed to lubricate and protect equipment. After spraying turn can upside down and spray until nozzle is clear.

Manufactured exclusively by:
ABC COMPOUNDING CO., INC. • P. O. Box 16247 • Atlanta, GA 30321
770-968-9222 • 800-795-9222 • www.abccompounding.com
AERO is a registered trademark of ABC Compounding Co., Inc.

HIGHLIGHTS

- Very tacky - does not slip off
- Effective at high temperatures
- Protects against excessive wear
- Inhibits corrosion

TYPICAL PROPERTIES

- Specific Gravity: 0.86
- Propellant: Hydrocarbon
- Spray Characteristics: Coarse spray
- Appearance: Dark liquid
- Odor: Solvent
- Net Weight: 12 ounces

SAFETY CAUTIONS

Keep out of reach of children. Read label and SDS before use. Extremely flammable aerosol. Contains gas under pressure; may explode if heated. May be fatal if swallowed and enters airways. May cause drowsiness or dizziness. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation.

Refer to SDS for additional safety information.

