AERO® Live Bacteria / Enzymes products contain a synergistic blend of engineered bacterial strains for effective removal of various organic soils.





Grease Trap & Drain Line Maintainer Bathroom Cleaner & Deodorizer

Multi bacterial spore blend
Rapid bacteria replication

SURVIVORS® digests and liquefies organic waste, grease and food by-products and is non-toxic, non-acid, non-alkaline, and non-pathogenic. Survivors® will eliminate odors created by organic waste in urinals, toilet bowls, carpets and drains. Used periodically, Survivors® will serve to keep drains free of stoppage caused by organic waste. In addition, Survivors®, with an excess of 100 billion microorganisms per gallon, effectively degrades solid waste that accumulates in lift stations, septic tanks, porta-toilets, and drain pipes.

DIRECTIONS

GREASE TRAPS: For best results, start treatment immediately after the grease trap has been pumped. At the close of business, run lukewarm water down each drain leading to the grease trap for 5 seconds to clear the line. Dilute the recommended dose of product in enough lukewarm water to pour approximately 1/2 pint of the dilution down each drain. Let mixture stay in the drains overnight. Recommended dosage: 1 pint per day for 200 gallon traps; 2 - 3 pints for 500-1500 gallon traps; 2 - 3 quarts for traps larger than 1500 gallons. Dosing rates may vary based on grease loading. DRAIN LINES: Add 8 oz./in. diameter of drain directly to any drain and 2 oz./in. diameter of drain twice a week thereafter. To treat lines and pipes, begin on the first floor and proceed upward as the condition is brought under control. SEPTIC TANKS: Use 1 pint per 25 cu. ft. capacity for the initial dose. Pour into toilet and flush. Thereafter, use 8 oz. per week. If the septic tank has become clogged and odorous, add 1 gal. directly to the septic tank. After the tank functions properly, begin preventive maintenance schedule. **RECREATIONAL** VEHICLES: Add 2 oz. per gal. of water in the toilet holding tank. Thereafter, use 1 oz. per gal. as needed. Repeat after every cleanout. For use at a dump station, add 1 gal. per 50 gallons of tank capacity followed by 1 pint per week. Repeat after every cleanout. CARPETS: Test for colorfastness first. To eliminate odors resulting from organic waste, dilute 1 to 1 with warm water, let soak for at least 30 minutes and rinse thoroughly. May also be used in bonnet or extraction cleaning equipment by adding 1 qt. to a rinse tank. BATHROOMS: Dilute 1 to 10 for general cleaning of floors, walls, toilets, and urinals. For odor control, dilute 1 to 2 with warm water and spray in and around urinals, toilets, and other problem areas.

Manufactured exclusively by: ABC COMPOUNDING CO., INC. • P. O. Box 16247 • Atlanta, GA 30321 770-968-9222 • 800-795-9222 • www.abccompounding.com AERO is a registered trademark of ABC Compounding Co., Inc.

HIGHLIGHTS

- Rapid bacteria replications
- Reduces suspended solids
- Reduces sludge volume
- Reduces BOD
- Non-pathogenic

TYPICAL PROPERTIES

- pH: 8.7
- Specific Gravity: 1.0
- Appearance: White
- Fragrance: Cucumber Melon
- Bacteria Count: 100 billion/gallon

SAFETY CAUTIONS

Keep out of reach of children. Read label and SDS before use. Flammable liquid and vapor.

Refer to SDS for additional safety information.

