


AERO® Municipal Products are effective degreasers and deodorants for sewage treatment facilities.



aero

Digest Assist Lift Station Floating Degreaser

Frees hung-up or stuck floating digestion covers by merely applying around outer perimeter of cover and immediately wetting with ordinary garden hose.

DIRECTIONS

May be used as a preventative maintenance measure. To do this drip product in the influent at the rate of 1/4 to 1-1/2 ppm. (45 drops per minute equals one gallon in 24 hours). A simple water gate valve will maintain drip once set, as low as one pint per day. Drip directly into wet wells and lift stations. Add directly to sewer lines and force mains to remove grease build-up.

Eliminates grease or scum cakes in digester. Introduce through top digester in any port or inspection holes; 20 to 25 gallons is a good average guideline to follow. After introducing add 500 to 2000 gallons of water, continue to wet down top of grease cake daily. After treating digester, add 1 to 2 gallons daily in sludge compartments. In doing this you are working on the grease cake from top to bottom. After adding through sludge compartment continue circulation as usual.

Manufactured exclusively by:
ABC COMPOUNDING CO., INC. • P. O. Box 16247 • Atlanta, GA 30321
770-968-9222 • 800-795-9222 • www.abccompounding.com
AERO is a registered trademark of ABC Compounding Co., Inc.

HIGHLIGHTS

- Aggressive floating degreaser
- Petroleum distillate-based

TYPICAL PROPERTIES

- Specific Gravity: 0.80
- Appearance: Clear red liquid
- Odor: Hydrocarbon

SAFETY CAUTIONS

Keep out of reach of children. Read label and SDS before use. May be fatal if swallowed and enters airways. May cause drowsiness or dizziness. Causes skin and serious eye irritation. Flammable liquid and vapor.

Refer to SDS for additional safety information.

