AERO® Municipal Products are effective degreasers and deodorants for sewage treatment facilities.





Cherry Sewer Degreaser

- Digesters Sewer Lines
- Wet Wells Pumping Stations

WILL LIQUIFY AND CONTROL NORMAL GREASE CAKE, SCUM, FOAM & SURFACE ORGANIC BUILD UP

A special blend of solvents and biodegradable emulsifiers formulated especially for sewage treatment. If used properly, This product will liquify and control normal grease cake, scum, surface organic build-up, foam, etc. on the surface and walls of sewage treatment vessels.

DIRECTIONS

DIGESTERS- Introduce through ports or inspection holes at top of digester (20 to 30 gallons - more if needed) then add 500 to 2000 gallons of water to wet down grease and scum cake. Continue to wet down cake daily, then add 2 gallons in sludge compartment to attack grease from bottom.

STUCK FLOATING DIGESTER COVERS- Add digest aide around outer perimeter of cover and immediately wet down with pressure. Continue until cover is free.

WET WELLS, PUMPING STATIONS, AND SEWER LINES- Drip directly into wet wells and pumping stations. Add directly into sewer lines and force mains to remove grease build up.

PREVENTIVE MAINTENANCE- Drip digest aide into influent at rate of 1/4 to 1 1/2 ppm (45 drops/min. equals one gallon in 24 hours). Add 3-4 gallons weekly to lift stations.

HIGHLIGHTS

- Water-based degreaser
- Economical

TYPICAL PROPERTIES

Specific Gravity: 1.05

• pH: 13.0

• Appearance: Dark amber liquid

• Fragrance: Cherry

SAFETY CAUTIONS

Keep out of reach of children. Read label and SDS before use. Causes severe skin burns and eye damage. May be corrosive to metals.

Refer to SDS for additional safety information.

