

AERO® Sewer Solvent is excellent for opening sewers clogged by grease, rags, paper and other organic material.



aero

Red Hot Sewer Solvent

DIRECTIONS FOR USE

Wear protective gloves, face mask, splash proof goggles; and other protective clothing to avoid eye or skin contact.

Pour small amount into drain at manhole opening making sure all precautions are taken to avoid injury. After 15 minutes run plenty of water through drain. Use sewer solvent at regular intervals to keep sewers open. Do not stand over opening after pouring in the solution.

**DO NOT ADD HOT WATER.
DO NOT USE AROUND OPEN FLAME.**

WARNING: CARELESS USE CAN CAUSE SEVERE BURNS TO SKIN AND EYES.

Exposure: Severity of injury depends largely on product concentration and duration of exposure. Immediate action is necessary to limit severity of injury. Can cause minor irritation to severe burns and tissue damage to exposed areas of the body. May be harmful or fatal if swallowed.

HIGHLIGHTS

- Temperature of 20% aqueous solution: 215° F
- Time to reach maximum temperature: 1 min. 30 sec.
- Time to sustain temperature of 180°F: 7 min.

TYPICAL PROPERTIES

- Sodium Hydroxide (granulated caustic): 67%
- pH (1% solution): 12.9-13.2
- Aluminum: 8%
- Appearance: Red granular
- Odor: Odorless
- Bulk Density: 72-80 lbs/ft.

SAFETY CAUTIONS

Keep out of reach of children. Read label and SDS before use. Causes severe skin burns and eye damage. May be corrosive to metals.

Refer to SDS for additional safety information.

Manufactured exclusively for:

Aero Chemical Co., division of ABC Compounding Co., Inc.
P. O. Box 16247, Atlanta, GA 30321 • 770-968-9222
800-795-9222 • www.abccompounding.com



Nonfood Compounds
Program Listed L1
Registration # 134728