

Ultra Bright floor finish

ULTRA BRIGHT Floor Finish is based on the latest metal-free technology. It is a hard acrylic formulation, providing very high put-down gloss and good durability. It may be used with conventional low-speed or mop/recoat programs as well as with high speed burnishing equipment. This product was designed to work together with a certified floor finish remover in an environmentally preferable system of overall floor care. It can also be used with another equally efficacious stripper.

Advantages over conventional metal interlock finishes- GREAT REMOVABILITY, FASTER DRYING TIME, BETTER DURABILITY, NO AMMONIA ODOR and BETTER RE-COATABILITY

APPLICATION (new or existing floors): Thoroughly strip floor finish. Rinse floor thoroughly with clean water. Apply a sealer base (optional) to worn floors or high traffic floors to improve wear-resistance and enhance gloss. Apply ULTRA BRIGHT in uniform thin coats allowing time to dry thoroughly between coats. If a sealer is used, apply up to four coats. If a sealer is not used, apply four coats for best results. Allow for longer drying time in damp weather.

MAINTENANCE: Sweep as necessary. Damp mop or scrub lightly with a mild, neutral detergent. Spray buff or buff lightly with appropriate pad. Also excellent for high-speed buffing. In high traffic areas, re-coat worn spots as necessary.

SAFETY CAUTIONS: KEEP OUT OF REACH OF CHILDREN. It is recommended that protective gloves and safety glasses be worn when using this product. Make sure there is adequate ventilation. Refer to SDS for additional safety information.

Store in a cool dry place. Keep container closed when not in use. Dispose of contents and container in accordance with all local, regional, and national regulations.

TYPICAL PROPERTIES:

Specific Gravity: 1.02 20% Solids: рН: 7-8 Leveling: Excellent Film formation: Excellent Excellent Gloss: Water resistance: Excellent Detergent resistance: Excellent Removability: Excellent Black heal mark resistance: Very good Appearance: White emulsion Odor: Mild acrylic



This product meets Green Seal™
Standard GS-40 based on effective
performance and protective limits on VOCs
and human and environmental toxicity.
GreenSeal.org.



Manufactured exclusively by:
ABC COMPOUNDING CO., INC.
Earth Force Ltd. is a registered trademark of
ABC Compounding Co., Inc. PO Box 80729
Conyers, GA 30013 1-800-795-9ABC
www.abccompounding.com



