

AERO® D'Limonene Degreasers are designed for a broad range of applications from light-duty institutional cleaning to heavy-duty industrial degreasing.



aero®

Float

Floating Grease & Scum Solvent Sewage Digester

- CFC free
- Economical
- Floating degreaser
- Pleasant citrus fragrance
- Slow evaporation

DIRECTIONS

For Grease Traps:

1. Start treatment immediately after the grease trap has been pumped. Add one quart per cubic foot of capacity, then begin preventive maintenance schedule one week later. Repeat procedure after pumping.

2. For traps where scum blankets & grease cakes have already formed add one gallon per cubic foot directly to the grease trap. Repeat every 3 to 4 days until the scum blanket is liquefied.

Preventive Maintenance: One (1) gallon daily per 40 cubic feet of trap capacity.

For Pumping Stations, Wet Wells, & Sewer Lines: Add 1% - 5% by volume (i.e. 1-5 gallons per 100 gallons of capacity) as initial treatment. For preventive maintenance (daily application) use 0.25% (i.e. 1 quart per 100 gallons of capacity).

Solvent Cleaner: This product is a solvent for removal of many printing inks, rosins, ester gums, alkyd resins, tar and asphalt. Test on an inconspicuous area before using on painted surfaces.

Manufactured exclusively by:
ABC COMPOUNDING CO., INC. • P. O. Box 16247 • Atlanta, GA 30321
770-968-9222 • 800-795-9222 • www.abccompounding.com
AERO is a registered trademark of ABC Compounding Co., Inc.

HIGHLIGHTS

- Excellent for degreasing
- Pleasant citrus fragrance
- Floating degreaser
- No petroleum distillates
- Slow evaporation

TYPICAL PROPERTIES

- Specific Gravity: 0.81
- Dilution: Ready to use.
- Appearance: Green
- Odor: Citrus

SAFETY CAUTIONS

Keep out of reach of children. Read label and SDS before use. May be fatal if swallowed and enters airways. May cause drowsiness or dizziness. Causes skin and serious eye irritation. May cause an allergic skin reaction. Flammable liquid and vapor.

Refer to SDS for additional safety information.

