

AERO® brand aerosols are the finest available anywhere. A full range of solutions, from cleaning, to pest control. No other products can match our standards or our commitment to quality.



aero®

Moli-Lube Dry Lubricant Spray

- **Reduces Friction / Retards Wear**
- **Effective up to 1000°F**
- **Excellent Under High Pressure Loads**

MOLI-LUBE is a dry molybdenum disulfide and graphite product that keeps machined metal from oxidizing and lubricates in extreme environments. MOLI-LUBE will not wash off. Once it dries, it will stay in place providing lubricity even under very heavy loads (in excess of 20,000 psi). Excellent for oil field pipe threads. Effective up to 1000°F.

Recommended for: Reducing sliding friction, chain/sprocket lubrication, release agent, door locks/hinges, lathe bed and rails, machine shops.

DIRECTIONS FOR USE

Shake well before using. Clean surface thoroughly. Hold can 6 to 8 inches from surface and apply even, thin coats. Allow 1 to 5 minutes for adequate drying. The concentration of solids in this product may clog nozzle. Shake vigorously and often. Before storing, turn can upside down and spray until nozzle is clear.

HIGHLIGHTS

- Reduces friction / Retards wear
- Effective up to 1000°F
- Excellent under high pressure loads

TYPICAL PROPERTIES

- Specific Gravity: 0.76
- Propellant: Hydrocarbon
- Spray Characteristics: Coarse spray
- Appearance: Dark liquid
- Odor: Solvent
- Net Weight: 13 ounces

SAFETY CAUTIONS

Keep out of reach of children. Read label and SDS before use. Extremely flammable aerosol. Contains gas under pressure; may explode if heated. May be fatal if swallowed and enters airways. May cause drowsiness or dizziness. Causes skin irritation. Causes serious eye irritation.

Refer to SDS for additional safety information.



Manufactured exclusively by:
ABC COMPOUNDING CO., INC. • P. O. Box 16247 • Atlanta, GA 30321
770-968-9222 • 800-795-9222 • www.abccompounding.com
AERO is a registered trademark of ABC Compounding Co., Inc.

4676TDS.071217