



Atlanta, GA / Dallas, TX

Safety Data Sheet

C-635 Hydraulic Fluid

Section 1 Identification

Trade Name: C-635 Hydraulic Fluid
Product Identification: 4010
Synonyms: Solvent blend
Product Use Description:
Lubricant


General Info Phone: (800) 795-9222
Emergency Phone: (800) 535-5053

Supplier:
ABC COMPOUNDING CO. INC.
6970 JONESBORO RD
Morrow, GA 30260

Section 2 Hazards Identification

Classifications

Aspiration Hazard - Category 1
Skin Sensitization - Category 1
Flammable Aerosols - Category 1
Gasses under pressure - Liquefied gas



Signal Word: Danger

Hazard Statements

Keep out of reach of children.
Read label and SDS before use.
May be fatal if swallowed and enters airways.
Extremely flammable aerosol
Contains gas under pressure; may explode if heated.
May cause an allergic skin reaction

Precautionary Statements

Prevention

Keep away from heat, sparks, open flames and hot surfaces. ☐ -No smoking.
Do not spray on an open flame or other ignition source.
Pressurized container: Do not pierce or burn, even after use.
Avoid breathing mist/spray.
Wear protective gloves.
Contaminated work clothing must not be allowed out of the workplace.

Response

IF SWALLOWED: Immediately call a poison center or a doctor. Do NOT induce vomiting.
IF ON SKIN: Wash with plenty of soap and water. Wash contaminated clothing before reuse.
If skin irritation or rash occurs get medical attention.

Storage

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
Store in a well-ventilated place.
Store locked up.



Atlanta, GA / Dallas, TX

Safety Data Sheet

C-635 Hydraulic Fluid

Disposal

Dispose of contents and container in accordance with all local, regional, and national regulations.

Hazards Not Otherwise Specified

Not applicable

Section 3 Composition

<u>Chemical Name</u>	<u>CAS #</u>	<u>Concentration % by Weight</u>
Hydrotreated Middle Petroleum Distillate	64742-46-7	>=8 <= 15
Hydrotreated Petroleum Distillate	64742-47-8	>=8 <= 15
Hydrotreated Light Naphthenic Petroleum Distillate	64742-53-6	>=40 <= 60
1-Decene, mix of tetramer and trimer, hydrogenated	68649-12-7	>=4 <= 10
Isobutane	75-28-5	>=20 <= 25
Sulfonic acids, petroleum, barium salts	61790-48-5	>=1 <= 5
Solvent-refined Heavy Paraffinic Petroleum Distillate	64741-88-4	>=1 <= 5
Propane	74-98-6	>=1 <= 5
Benzenesulfonic acid, di-C10-18-alkyl derivs., barium salts	93820-55-4	>=1 <= 5
Triphenyl phosphate	115-86-6	>=0.1 <= 1
2,6-di-tert-butyl-p-cresol	128-37-0	>=0.1 <= 1
Isobutylated phenol, phosphate (3:1)	68937-40-6	>=0.1 <= 1

Section 4 First Aid

EMERGENCY OVERVIEW

DANGER. Extremely flammable aerosol. Contents under pressure. Harmful or fatal if swallowed. Aspiration hazard if swallowed.

Keep away from heat and flame.

EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.

SKIN: Wash with plenty of soap and water.

INHALATION: Remove person to fresh air and keep comfortable for breathing. Call a poison center or a doctor if you feel unwell.

INGESTION: Harmful or fatal if swallowed. Seek medical attention immediately. Aspiration hazard - this material can enter lungs during swallowing or vomiting and cause lung inflammation and damage.

Section 5 Fire Fighting Measures



Safety Data Sheet

C-635 Hydraulic Fluid

Suitable fire extinguishing media:

Use water spray, fog or foam.

Specific hazards arising from the chemical:

Flammable aerosol. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of subsequent explosion. Gas may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back, causing fire or explosion. Bursting aerosol containers may be propelled from a fire at high speed.

Hazardous thermal decomposition products:

Carbon Dioxide, Carbon Monoxide

Specific fire-fighting methods:

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Special protective equipment for fire fighters:

Fire fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in a positive pressure mode.

Section 6 Accidental Release Measures

Personal precautions:

Put on appropriate personal protective equipment (see section 8)

Environmental precautions and clean-up methods:

Stop all leaks. Isolate hazard area. Keep unnecessary and unprotected personnel from entering. Eliminate all ignition sources. Disperse vapors with water spray. Prevent runoff from entering drains, sewers, streams or other bodies of water. Absorb spill with inert material. Absorb unrecoverable product. Transfer contaminated absorbent, soil and other materials to containers for disposal.

Section 7 Handling and Storage

Do not use or store near heat, sparks or open flame. Exposure to temperatures above 120 F may cause bursting. Do not puncture or incinerate container. Store in a cool, dry place. Do not get in eyes, on skin or on clothing. Intentional misuse by deliberately concentrating and inhaling may be harmful or fatal. Keep out of reach of children.

Section 8 Exposure Controls/Personal Protection

1-Decene, mix of tetramer and trimer, hydrogenated

NIOSH	5 mg/m ³
OSHA PEL	5 mg/m ³

2,6-di-tert-butyl-p-cresol

NIOSH	10 mg/m ³
OSHA PEL	10 mg/m ³

Hydrotreated Light Naphthenic Petroleum Distillate

ACGIH TLV	5 mg/m ³
OSHA PEL	5 mg/m ³

Hydrotreated Middle Petroleum Distillate

OSHA PEL	500 ppm
----------	---------



Atlanta, GA / Dallas, TX

Safety Data Sheet

C-635 Hydraulic Fluid

Hydrotreated Petroleum Distillate	
OSHA PEL	100 ppm
Isobutane	
ACGIH TLV	1000 ppm
Propane	
ACGIH TLV	1000 ppm
Solvent-refined Heavy Paraffinic Petroleum Distillate	
ACGIH TLV	5 mg/m3
OSHA PEL	5 mg/m3
Triphenyl phosphate	
ACGIH TLV	3 mg/m3
OSHA PEL	3 mg/m3

Eye Protection: Wear safety glasses or goggles.

Skin Protection: To prevent repeated or prolonged contact, wear impervious gloves (made from rubber, nitrile or neoprene).

Respiratory Protection: When respiratory protection is required use an organic vapor cartridge. A respiratory program that meets OSHA's 29 CFR 1910.34 & ANSI Z88.2 requirements must be followed.

Engineering Controls: Good general ventilation required.

Section 9 Physical and Chemical Properties

Property	Value		
Appearance	SPRAY/MIST	Auto Ignition Temp	NOT AVAILABLE
Boiling Point	NOT AVAILABLE	Color	AMBER
Decomposition Temperature	NOT AVAILABLE	Evaporation Rate	NOT AVAILABLE
Explosive Limit Ranges	NOT AVAILABLE	Explosive Properties	NOT AVAILABLE
Flash Point	94 C	Melting/Freezing Point	NOT AVAILABLE
Odor	SLIGHT SOLVENT	Odor Threshold	NOT AVAILABLE
Other Information	NOT AVAILABLE	Oxidizing Properties	NOT AVAILABLE
Partition Coeff	NOT AVAILABLE	Physical State	LIQUID
Relative Density	0.88	Solubility (Water)	INSOLUBLE
Vapor Density	NOT AVAILABLE	Vapor Pressure	NOT AVAILABLE
Viscosity	13.4 MM2/S (40 C)	pH	NOT APPLICABLE

Section 10 Stability and Reactivity

Reactivity :	Under normal conditions of storage and use, hazardous reactions will not occur.
Chemical Stability :	Stable under normal conditions.
Incompatible Materials :	Acids and strong oxidizers
Conditions to Avoid :	High temperatures, open flames, sparks, welding.
Decomposition Products:	CO, CO2

Section 11 Toxicological Information

Primary Route of Entry: Skin contact, inhalation

Acute/Potential Health Effects:

EYES: May cause eye irritation. Symptoms include stinging, tearing and redness.

SKIN: May cause skin irritation.

INHALATION: High vapor concentrations may be irritating to respiratory tract.



Safety Data Sheet

C-635 Hydraulic Fluid

INGESTION: Harmful or fatal if swallowed. Aspiration hazard - this material can enter lungs during swallowing or vomiting and cause lung inflammation and damage.

Chronic / Long Term Effects: None known.

Target Organ Effects: None known.

Reproductive/Developmental Information: Not available.

Carcinogenic Information: This material is not listed as a carcinogen by IARC, NTP or OSHA.

Acute Toxicity Values:

Not available.

Section 12 Ecological Information

Not available.

Section 13 Disposal Considerations

Waste must be disposed of in accordance with federal, state and local environmental control regulations. See label for further instructions.

Section 14 Transport Information

Certain shipping modes or package sizes may have exceptions from the transport regulations. The classification provided may not reflect those exceptions and may not apply to all shipping modes or package sizes.

UN number 1950
Proper shipping name Aerosols, flammable
Class 2.1
Packing group -

Section 15 Regulatory Information

Section 313 of Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 (40 CFR 372.65)

Benzenesulfonic acid, di-C10-18-alkyl derivs., barium salts
Sulfonic acids, petroleum, barium salts

If identified components of this product are **CERCLA** hazardous substances and/or listed under **Sections 302, 304, or 313 of Title III** of the Superfund Amendments and Reauthorization Act (SARA) of 1986 (also known as EPCRA, the Emergency Planning and Community Right-To-Know Act), or under **California Proposition 65** (Safe Drinking Water and Toxic Enforcement Act), they are listed above in Section 15 of this SDS.

If identified components of this product are listed under Section 313, this product contains toxic chemicals subject to the reporting requirements of Section 313. This information must be included in all SDS that are copied and distributed for this material.

Title III Section 311/312 Hazardous Categories - 40 CFR 370.2:

ACUTE (X) Chronic () Fire (X) Pressure (X) Reactive () Not Applicable ()

T.S.C.A. Status: All chemical substances found in this product comply with the Toxic Substances Control Act inventory reporting requirements.



Safety Data Sheet

C-635 Hydraulic Fluid

RCRA Status: Under RCRA, it is the responsibility of the product user to determine at the time of disposal, whether a material containing the product or derived from the product should be classified as a hazardous waste. If this product becomes hazardous waste it would be assigned RCRA Code(s)

None

Section 16 Other Information

HMIS Ratings :

HEALTH	2
FLAMMABILITY	4
REACTIVITY	0
PERSONAL PROTECTION	B

Disclaimer: This Manufacturer believes that the information contained in the Safety Data Sheet is accurate. The suggested procedures are based on experience as of the date of the publication. They are not necessarily all inclusive nor fully adequate in every circumstance. Also, the suggestions should not be confused with, nor followed in violation of applicable laws, regulations, rules or insurance requirements.

Preparation/Revision Date: 7/23/15