



Cutting & Tapping Fluid

CLINGING COOLANT and LUBRICANT FOR MACHINING OPERATIONS

CUTTING & TAPPING FLUID is a special blend of synthetic oils and thickening agents, this product remains on the cutting bit even under extreme pressures. Keeps operating temperatures cool. Protects from rust and corrosion. Not recommended for use on copper or aluminum.

DIRECTIONS

Shake well before using. Hold nozzle 6 to 8 inches from surface requiring lubrication. Generously spray onto cutting surface or tool. Reapply as necessary to maintain lubrication level.

AERO brand aerosols are the finest available anywhere. A full range of solutions, from cleaning, to pest control. No other products can match our standards or our commitment to quality.

HIGHLIGHTS

- Clinging formulation
- Lubricates and cools
- Inhibits corrosion

TYPICAL PROPERTIES

- Specific Gravity: 0.885
- Propellant:: Hydrocarbon
- Spray Characteristics: Foaming spray
- Appearance: Brown liquid
- Odor: Solvent
- Net Weight: 16 ounces

SAFETY CAUTIONS

Keep out of reach of children.
Read label and SDS before use.
Extremely flammable aerosol.
Pressurized container: May burst if heated. May be fatal if swallowed and enters airways. May cause drowsiness or dizziness. Causes skin irritation. Causes serious eye irritation.

Refer to SDS for additional safety information.



Manufactured exclusively by:
ABC COMPOUNDING CO., INC.

P. O. Box 16247 • Atlanta, GA 30321 ☎ 770-968-9222 • 800-795-9222

abccompounding.com



84678TECH 052925